


Connector

Part number: 75011



MENNEKES
Elektrotechnik GmbH & Co. KG

Aloys-Mennekes-Straße 1
57399 Kirchhundem
GERMANY

www.MENNEKES.org

Product Description

- highly heat resistant contact carrier, silver plated contacts
- protection against kinking
- strain relief
- with cable gland
- MetalLine
- aluminium enclosure
- sea water resistant products are available on request
- if required, pilot cables can be introduced separately into plugs, please add "PK" to the part number

Technical Details

Connector	75011
Ampere	250A
Number of poles	4p
Clock position	6h
Nominal voltage AC	400V
Nominal frequency	50 - 60 Hz
Protection type IP	IP67
Contact carrier	highly heat resistant contact carrier, silver plated contacts
X-CONTACT	no
Connection	cage terminals
Contact screw drive	allen key
Tightening torque connection terminal	16 Nm
Recommended wire end treatment for supply cable connection terminal	usable with and without ferrule
Strip length jacket	200 mm
Strip length conductor PH + N	60 mm
Strip length conductor PE	60 mm
Pilot contact	2 pilot contact
Conductor cross-section min.	70 mm ²
Conductor cross-section max.	240 mm ²
Conductor cross-section pilot max.	4 mm ²
Cable kink protection	integrated in strain relief

Connector	75011
Protective grommet	without protective grommet
Militärausführung	nein
Weight (net)	11000 g
Packaging unit	1 pcs
Quantity per pallet	18 pcs
EAN / identification number	4015394054979

Permissible ambient conditions		
	Min.	Max.
Permanent ambient temperature	-40 °C	100 °C

Material properties	
Housing	aluminium grey [no RAL colour code]
Hinged lid	metal grey [no RAL colour code]
Clamp basket	metal grey [no RAL colour code]
Fastening	plastic black [no RAL-colour code]

Material resistance

The material resistance overview can be found on the website in the section “Knowledge” - “Product knowledge” - “Materials”.

Material and enviromental properties	
RoHS 2011/65/EU incl. 2015/863/EU	✓
POP regulation (EU) 2019/1021	✓
Halogen-free	yes

Regulations and Standards

Norm	DIN EN IEC 60309
Declaration of Conformity	CE
Test label	EAC

Dimensional Drawing

Drawing
3 MB 54/1

Dim. in mm

